

VIP-ACK-600-SLIM



Overview	Specifications	Configure	Dimensions	Download
<b>User Capacity</b>		<b>600</b>		
Common Users		598		
Panic Users		2		
<b>Operating Voltage</b>		<b>12~28V AC/DC</b>		
Idle Current		< 65mA		
Active Current		< 100MA		
<b>Proximity Card Reader</b>		<b>HID &amp; EM &amp; Mifare</b>		
Radio Technology		125KHz & 13.56Mhz		
Read Range		2~6 cm		
<b>Wiring Connections</b>		Relay output, exit button, alarm, door contact, Wiegand input, Wiegand output		
<b>Relay</b>		<b>One (NO, NC, Common)</b>		
Adjustable Relay Output Time		0~99 Seconds (5 seconds default)		
Lock Output Load		2 Amp Maximum		
<b>Wiegand Interface</b>		<b>Wiegand 26~37bits</b>		
Wiegand Input		26~37bits		
Wiegand Output		26~37bits		
PIN Output		4 bits, 8 bits(ASCII), 10 digits Virtual Number		
<b>Environment</b>		<b>Meets IP66</b>		
Operating Temperature		-40 °C ~ 60 °C (-40 °F ~ 140 °F)		
Operating Humidity		0%RH ~ 98%RH		
<b>Physical</b>		<b>Zinc-Alloy Enclosure</b>		
Surface Finish		Powder Coat		
Dimensions		L150xW51xH23mm		
Unit Weight		500g		
Shipping Weight		600g		