

# VIP-ACK-1000-V



Overview **Specifications** Configure Dimensions Download

<b>User Capacity</b>	<b>1000 Card/PIN (990 Normal Users + 10 Visitor Users)</b>
<b>Operating Voltage</b> Idle Current Active Current	<b>12~28V AC/DC</b> 55mA 80mA
<b>Keypad</b> PIN length	<b>12 Key (3*4)</b> 4 ~ 6 digits
<b>Proximity Card Reader</b> Radio Technology Read Range	<b>EM/Mifare (Optional)</b> 125KHz EM/ 13.56MHz Mifare Card 3 ~ 6 cm
<b>Wiring Connections</b>	Electric lock, exit button, DOTL, external alarm, Wiegand (in/out)
<b>Relay</b> Adjustable Relay Output Time Adjustable Alarm Output Time Lock Output Load Alarm Output Load	<b>ONE (NO, NC, COM)</b> 0 ~ 99 Seconds (5 seconds default) 0 ~ 3 minutes (1 minute default) 3 Amp Maximum 3 Amp Maximum
<b>Wiegand Interface</b>	Wiegand 26 bit input/output
<b>Environment</b> Operating Temperature Operating Humidity	<b>Meets IP66</b> -40°C ~ 60 °C (-40 °F ~ 140 °F) 10% ~ 90% Non-Condensing
<b>Physical</b> Surface Finish Dimensions Unit Weight Shipping Weight	<b>Zinc-Alloy Enclosure</b> Powder Coat 11.7L x 7.6W x 2.5H (cm) 600g 700g